Contract NASW-1527

20 September 1967

Quarterly Report No. 2 May 16 - August 15, 1967

Prepared By
S. Matsuda, B. P. Sullivan,
and S. Polansky

Prepared for National Aeronautics and Space Administration Headquarters Washington, D.C., 20546

MONSANTO RESEARCH CORPORATION
BOSTON LABORATORY
Everett, Massachusetts 02149

N67-39069

(ACCESSION NUMBER) — (TURU)

(ACCESSION NUMBER) — (TURU)

(TURU)

(TURU)

(TURU)

(TURU)

(TURU)

(TURU)

(TURU)

FACILITY FORM 602

TABLE OF CONTENTS

	<u> </u>	age
I.	Summary	1
II.	Introduction	2
III.	Preparation of Electrodes	3
IV.	Test Results	4
	A. Corrosion Testing	4
	B. Dextrose Oxidation	4
	C. N_2H_4 Oxidation	4

I. SUMMARY

During the second quarter of the contract, the second group of compounds supplied by the U. S. Bureau of Mines was tested for catalytic activity in the oxidation of N_2H_4 . Some compounds showed very high activity in the oxidation of N_2H_4 , although all compounds corroded in the test electrolyte solution.

Selected catalysts from the first group were further examined for their characteristics on the $\rm N_2H_4$ anode. The most interesting result was the extremely high $\rm NH_3$ content in the gas evolved from these electrodes.

II. INTRODUCTION

The objective of this contract is to determine certain essential properties of non-noble metal compounds as electrode catalysts for fuel cells. Properties of major interest include: polarization characteristics of the electrodes containing these compounds; and the chemical stability of these electrodes in prescribed test environments.

The work undertaken at Monsanto Research Corporation is to investigate the electrocatalytic activity of the compounds for oxidation of dextrose and hydrazine.

During the first quarter, interstitial compounds, namely, carbide, nitride, carbonitride and nitrocarbide of iron were investigated. Results showed that no compounds were catalytically active for dextrose oxidation in buffered neutral electrolyte, but all compounds were sufficiently active for N_2H_4 oxidation in KOH electrolyte. Some compounds, particularly those prepared from leached Raney iron, however, showed significantly severe corrosion in the caustic electrolyte.

During this quarter, leached Raney alloys of Ni, Co and Ag, and their carbides and nitrocarbides were supplied by the U. S. Bureau of Mines. These were evaluated in the same manner as the first group of catalysts. Some additional experiments on some of the promising catalysts from the first group were also conducted.

III. PREPARATION OF ELECTRODES

All catalysts were preconditioned according to the procedure described in the first quarterly report.

Since one catalyst of the first group ignited during grinding, all catalysts of the second group were ground and sieved to -400 mesh in a chemically pure argon atmosphere prior to the final preconditioning process.

All electrodes prepared during the second quarter were type B*. These electrodes contain a network of macropores in a micro-porous matrix and are considered very suitable for the present study.

Catalyst loading was approximately 0.7g/inch2.

^{*} The method for preparing this type electrode is Monsanto Research proprietary.

IV. TEST RESULTS

A. CORROSION TESTING

Weighed samples (about 0.5 gram each) were soaked overnight in 50 cc of 5M KOH in a constant temperature bath at 70° C. The following day, they were collected by filtration, dried in vacuum, and weighed. All samples were found to have gained weight, perhaps due to formation of hydroxide or hydrated oxides on the surface of the powder. The samples containing cobalt formed a blue color in the test solution. The same tests were run in 5M KOH with 2M N_2H_4 added. However, the gas evolution produced by decomposition of hydrazine was so vigorous that portions of the samples were lost. Therefore, weighing after the corrosion tests was omitted. Coloring of the solutions was somewhat different from that in KOH without N_2H_4 .

Finally, the samples were tested in inhibited 0.1M HCl. In all cases, there was significant loss of weight. Most of the leached Raney alloys produced gas evolution as well.

Results are summarized in Table 1.

B. DEXTROSE OXIDATION

Evaluation of catalytic activity for dextrose oxidation was to be carried out under contract PH43-66-976, "Implantable Fuel Cell for an Artificial Heart", for the National Heart Institute, Department of Health, Education and Welfare.

Since contamination of the blood system due to corrosion of electrode material is impermissible, we determined that these catalysts are not appropriate for this application. Consequently, no experiments were carried out for this phase.

C. N₂H₄ OXIDATION

Although the corrosion tests revealed that most of the catalysts in the second group were attacked in some degree by the test electrolyte (5M KOH + 2M N_2H_4), the polarization data for N_2H_4 oxidation was taken in the manner described in the previous report.

IR free electrode potentials vs the saturated calomel electrode at various current densities above 10 mA/cm² (apparent densities) are given in Table 2. Results indicate that some catalysts are very active in $\rm N_2H_4$ oxidation. Eight catalysts were selected from the first group (interstitial compounds of

Table 1

CORROSION TESTS

KOH ZM N2H4	Weight	samples	not	weighed	after test	due to loss	by excessive	gassing of	the N ₂ H ₄		_																
Effect of 5M KOH 2M N ₂ H ₄	Color	None	None	Blue	Yellow	Yellow	Yellow	None	Yellow	None	None	Yellow	None	Yellow	Yellow	Yellow	None	None	Blue	None	None	Yellow	None	Yellow	None	None	Yellow
Effect of 0.1M HCl	Wt. Loss, %	7	9	21	10	7	10	19	14	18	23	27	=	evolved 27	21	23	22	26	evolved 33	evolved 28	evolved 33	23	26 evolved	28 olved	olved 25	evolved 13	s 20
	Color	None	None	None	None	None	None	None	None	None	None	None	None	Pink, gas ev	None	None	None	None	pink, gas ev	pink, gas ev	Pink, gas ev	None	None, rapid gas eve	Green, rapid gas evolved	Pink, gas evolved	Pink, gas ev	Green, no gas
5M KOH	Wt. Gain, %	∞	15	5	22	22	13	17	29	30	21	2 ·	12	18	53	17	27	20	13	16	11	25	4.1	Ξ	4	20	29
Effect of 5M KOH	Color	Blue	None	Pale blue	Pale blue	Pale blue	None	Pale yellow	Blue	None	Blue	Pale yellow	None	Blue	Pale blue	None	None	Pale yellow	Blue	Pale blue	Pale blue	Pale blue	Pale blue	Pale yellow	Blue	Blue	None
		ე-0ე	Ni-C	1Co:3Ag-C	1Co:1Ag-C	lNi:1Co-C	lNi:1Ag-C	3Ni:1Ag-C	Co-NC	Ni-NC	INi:1Co-NC	IN1:1Ag-NC	3Ni:lAg-NC	INi:1Co-RAL	3Ni:1Co-RAL	INi:3Ag-RAL	1Ni:1Ag-RAL	3Ni:lAg-RAL	1Co:3Ag-RAL	1Co:1Ag-RAL	3Co:1Ag-RAL	INI:1Co:1Ag-RAL	lNi:1Co:1Au-RAL	lNi:lAg:lAu-RAL	1Co:1Ag:1Au-RAL	Co-RC	Ni-RN
	Catalyst	330	350				430															RAL 10	RAL11		RAL13		RN2

C = carbide; NC = Nitrocarbide; RAL, RC, RN = leached Raney alloy

Table 2

POTENTIAL OF VARIOUS N_2H_4 ELECTRODE

vs.

THE SATURATED CALOMEL ELECTRODE AT VARIOUS CURRENT DENSITIES (IR FREE)

Electrode:

B Type

Electrolyte: $5M KOH + 2M N_2H_4$

Temperature: 70°C

			Curren	ies, m	mA/cm ²		
Catalys	<u>ts</u>	OCP	10	20	50	100	
33C	Co-C	-1.22	-1.22	-1.21	-1.21	-1.19	
35C	Ni-C	-1.19	-1.18	-1.16	-1.14	-1.12	
38C	1Co:3Ag-C	-1.17	-1.16	-1.16	-1.15	-1.09	
39C	1Co:1Ag-C	-1.22	-1.22	-1.22	-1.21	-1.21	
42C	lNi:1Co-C						
43C	lNi:lAg-C	-1.21	-1.21	-1.19	-1.19	-1.19	
46C	3Ni:1Ag-C	-1.23	-1.21	-1.20	-1.18	-1.18	
21NC	Co-NC	-1.23	-1.23	-1.20	-1.20	-1.19	
23NC	Ni-NC	-1.16	-1.13	-1.10	-1.09	-1.07	
28NC	lNi:lCo-NC	-1.16	-1.11	-1.09	-1.03	-0.85	
31NC	lNi:lAg-NC	-1.25	-1.25	-1.25	-1.21	-1.21	
32NC	3Ni:1Ag-NC	-1.19	-1.13	-1.12	-1.12	-1.12	
RAL2	lNi:1Co-RAL	-1.12	-1.12	-1.10	-1.10	-1.05	
RAL3	3Ni:1Co-RAL	-1.25	-1.25	-1.25	-1.23	-1.23	
RAL4	1Ni:3Ag-RAL	-1.20	-1.19	-1.19	-1.14	-1.12	
RAL5	lNi:lAg-RAL	-1.15	-1.15	-1.12	-1.12	-1.12	
RAL6	3Ni:1Ag-RAL	-1.15	-1.15	-1.15	-1.13	-1.10	
RAL7	1Co:3Ag-RAL	-1.24	-1.23	-1.22	-1.20	-1.16	
RAL8	1Co:1Ag-RAL	-1.23	-1.23	-1.20	-1.18	-1.17	
RAL9	3Co:1Ag-RAL	-1.25	-1.25	-1.25	-1.25	-1.25	
RAL10	lNi:lCo:lAg-RAL	-1.23	-1.23	-1.23	-1.20	-1.20	
RAL11	lNi:lCo:lAu-RAL	-1.23	-1.23	-1.23	-1.23	-1.23	
RAL12	1Ni:1Ag:1Au-RAL	-1.20	-1.19	-1.19	-1.19	-1.18	
RAL13	1Co:1Ag:1Au-RAL	-1.24	-1.23	-1.23	-1.22	-1.22	
RC1	Co-RC	-1.25	-1.25	-1.25	-1.24	-1.19	
RN2	Ni-RN	-1.16	-1.16	-1.16	-1.15	-1.15	

C = carbide; NC = nitrocarbide; RAL, RC, RN = leached Raney metal or alloy

iron) for further investigation. They were made into 2 x 2 inch B type electrodes having catalyst loadings of approximately 0.7 g/in.². The rate of gas evolution, composition of the evolved gas and electrode potentials for these electrodes were determined at open circuit and under polarization at 100 amp/ft². These data are specifically important in the practical operation of N_2H_4 -Air fuel cell systems.

Data are summarized in Table 3. The most interesting result from the data is the extremely high content of $\rm NH_3$ in the evolved gas. It is about 100 to 1000 times higher than the average $\rm NH_3$ content from the presently operating MRC $\rm N_2H_4$ -electrode. At present we do not have an established mechanism for $\rm NH_3$ formation on the $\rm N_2H_4$ anode. However, we suggest that these high $\rm NH_3$ contents may be due to unusually high activity of these compounds for breaking $\rm N_2$ bonding, as shown in the following equation:

$$H_2N:NH_2 \xrightarrow{catalyst} 2NH_2$$

where $2H^*$ are products of the local cathodic reaction on the N_2H_4 anode.

DISTRIBUTION LIST

New Technology Representative Office of Technology Utilization - Code UT NASA Headquarters Washington, D.C. 20546

Chief, Solar & Chemical Power Systems Code RNW NASA Headquarters Washington, D.C. 20546 (8)

Mr. D. Bienstock Bureau of Mines 4800 Forbes Avenue Pittsburgh, Pa. 15213

1 i

Dr. D. Pouli Allis-Chalmers Mfg. Co. 1100 S. 70th St. Milwaukee, Wisconsin 53214

Dr. Eugene Weissman General Electric Research Laboratory P. O. Box 1088 Schenectady, New York 11500

Or. George E. Evans Union Carbide Corporation Electronics Division P. O. Box 6116 Cleveland, Ohio 44101

Mr. Robert J. Flannery 910 South Michigan Avenue Chicago 80, Illinois Scientific and Technical Information Facilities P. O. Box 33 College Park, Maryland 20740

Attention: NASA Representative

Ernst M. Cohn Code RNW NASA Headquarters Washington, D.C. 20546

Dr. A. Makrides TYCO Laboratories Bear Hill Waltham, Mass. 02154

Dr. C. E. Heath Esso Research & Engineering Co. P. O. Box 8 Linden, New Jersey 07036

Dr. Seigo Matsuda Honsanto Research Corporation 1101 17th St., N.W. Washington, D.C. 20036

Dr. H. J. Goldsmith Catalyst Research Corporation 6101 Falls Road Baltimore, Maryland 21209